

AMENDMENTS TO THE CLAIMS

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A bending machine for bending a workpiece by cooperation of an upper bending mold and a lower bending mold which are relatively movable in ~~[[the]]~~ a vertical direction, comprising:

an upper table which has an upper mold attachment part ~~for-attaching which~~ attaches the upper bending mold on ~~[[the]]~~ a bottom side thereof and extends in ~~[[the ]]~~ a horizontal direction;

a lower table which is opposed to the upper table in the vertical direction, has a lower mold attachment part ~~for-attaching which~~ attaches the lower bending mold on ~~[[the]]~~ a top side thereof and extends in the horizontal direction;

an input part ~~for-inputting which~~ inputs product information;

a bending order determiner that determines a bending order of the workpiece;

a mold determiner that determines ~~[[the]]~~ a mold necessary for bending the workpiece;

a layout determiner that determines a layout of the mold;

a positioning information calculator that calculates a position of the workpiece with respect to the mold determined by the layout determiner as work position information; and

a navigating member ~~for navigating~~ which navigates a position of the workpiece to ~~[[the]]~~ a operator by movement in the horizontal direction on the basis of the work position information calculated by the positioning information calculator.

2. (Currently Amended) ~~[[A]]~~ The bending machine according to claim 1, wherein

the navigating member is provided on a front face of the lower table so as to be movable in the horizontal direction, has a striking face to which an end face of the workpiece can strike from the left or right direction; and

the navigating member can be freely moved in the direction of an upper face of a die after positioning in the horizontal direction.

3. (Currently Amended) ~~[[A]]~~ The bending machine according to claim 2, wherein

a locating member is provided at a front end of the navigating member and has a mounting table ~~for maintaining~~ which maintains a height of the workpiece appropriately when the workpiece is struck against an end face of the locating member.

4. (Currently Amended) ~~[[A]]~~ The bending machine according to claim 2, wherein

a locating member is rotatably mounted at the front end of the navigating member and by rotating the locating member and striking the workpiece against the end face of the locating member, position of the mold can be guided to the operator.

5. (Currently Amended) [[A]] The bending machine according to claim 1, wherein

the navigating member is a back gauge provided in the rear side of the lower table so as to be movable in the horizontal direction and [[the]] a longitudinal direction.

6. (Currently Amended) [[A]] The bending machine according to claim 1, wherein

the navigating member is a light-emitting device ~~for guiding~~ which guides the position of the workpiece to the operator by emitting light at an appropriate position.

7. (Currently Amended) [[A]] The bending machine according to claim 1, wherein

the navigating member is a belt with a navigating guide part and the navigating guide part stops at an appropriate position, thereby to guide the position of the workpiece to the operator.

8. (Canceled)

9. (Currently Amended) A bending machine for bending a workpiece by cooperation of an upper bending mold and a lower bending mold, comprising:

an upper table which has an upper mold attachment part ~~for attaching~~ which attaches the upper bending mold on ~~[[the]]~~ a bottom side thereof and extends in ~~[[the]]~~ a horizontal direction;

a lower table which is formed so as to be opposed to the upper table in ~~[[the]]~~ a vertical direction, has a lower mold attachment part ~~for attaching~~ which attaches the lower bending mold on ~~[[the]]~~ a top side thereof, extends in the horizontal direction and is movable in the vertical direction with respect to the upper table;

a navigating member which is provided on a front face of at least either of the upper table or the lower table so as to be movable in the horizontal direction and guides ~~[[the]]~~ an operator;

a traveling actuator ~~for transferring~~ which transfers the navigating member in the horizontal direction;

a mold layout determiner that determines mold layout information representing a layout mode of the lower bending mold and the upper bending mold in the horizontal direction on the basis of product information representing at least a shape of ~~[[the]]~~ a product;

a positioning information calculator ~~for calculating~~ which calculates work positioning information representing a positioning mode of the workpiece with respect to the lower bending mold on the basis of the product information and the mold layout information; and

a traveling actuator controller ~~for controlling~~ which controls the traveling actuator so as to locate the navigating member at a position corresponding to a work positioning reference position in the horizontal direction on the basis of the mold layout information.

10. (Currently Amended) [[A]] The bending machine according to claim 9, wherein

the navigating member is provided on a front face of the lower table so as to be movable in the horizontal direction, has a striking face to which an end face of the workpiece can strike from the left or right direction; and

the navigating member can be freely moved in the direction of an upper face of a die after positioning in the horizontal direction.